

DIESEL POWER MODULE

AIR CHARGE-AIR COOLING

Voltages:

1000 kWe / 60 Hz / Prime - 480V, 600V



SYSTEM RATINGS

Prime	DP1000D6SRA	DP1000D6SNA
Voltage (L-L)	480V	600V
Phase	3	3
PF	0.8	0.8
Hz	60	60
kW	1000	1000
kVA	1250	1250
AMPS	1504	1203
skVA@30%		
Voltage Dip	3200	2600
Generator Model	740RSL4046	741RSS4284
Temp Rise	105 °C/40 °C	105 °C/40 °C
Connection	4 LEAD WYE	4 LEAD WYE

CERTIFICATIONS AND STANDARDS

// **Emissions** – EPA Tier 2 Certified

// **Engine-generator set is designed and manufactured in facilities certified to standards ISO 9001:2008 and ISO 14001:2004**

// **Performance Assurance Certification (PAC)**

- Engine-Generator Set Tested to ISO 8528-5 for Transient Response
- Verified product design, quality and performance integrity
- All engine systems are prototype and factory tested

// **Power Rating**

- Accepts Rated Load in One Step Per NFPA 110
- Permissible average power output during 24 hours of operation is approved up to 75%.

STANDARD FEATURES*

- // MTU Onsite Energy is a single source supplier
 - // Global Product Support
 - // 2 Year Standard Warranty
 - // 18V2000 Diesel Engine
 - 35.8 Liter Displacement
 - 4-Cycle
 - // Engine-generator resilient mounted
 - // Complete Range of Accessories
- // Generator
 - Brushless, Rotating Field Generator
 - PMG (Permanent Magnet Generator) supply to regulator
 - 300% Short Circuit Capability
 - 2/3 Pitch Windings
 - Voltage Adjust Toggle Switch
 - // Digital Control Panel
 - UL Recognized, CSA Certified, NFPA 110
 - Complete System Metering
 - LCD Display
 - // Cooling System
 - Remote Mounted
 - Electrically Driven Fan

STANDARD EQUIPMENT*

// Engine

Air Cleaners – Heavy Duty Two Stage
 Oil Pump
 Oil Drain Extension & S/O Valve
 Full Flow Oil Filters
 Closed Crankcase Ventilation
 Jacket Water Pump
 Thermostats
 Radiator – Remote Mounted
 Electric Starting Motor – 24V
 Governor – Electronic Isochronous
 Base – Heavy Duty Construction
 SAE Flywheel & Bell Housing
 Charging Alternator – 24V
 Battery Rack & Cables
 Flexible Fuel Connectors
 Flexible Exhaust Connection
 EPA Certified Engine
 60 Hz

// Generator

NEMA MG1, IEEE and ANSI standards compliance for temperature rise and motor starting
 Sustained short circuit current of up to 300% of the rated current for up to 10 seconds
 Self-Ventilated
 Superior Voltage Waveform
 Digital, Solid State, Volts-per-Hertz Regulator
 No Load to Full Load Regulation

Brushless Alternator with Brushless Pilot Exciter
 4 Pole, Rotating Field
 105 °C Maximum Prime Temperature Rise
 2 Bearings
 Flexible Coupling
 Full Amortisseur Windings
 125% Rotor Balancing
 3-Phase Voltage Sensing
 ±0.25% Voltage Regulation
 100% of Rated Load – One Step
 3% Maximum Harmonic Content

// Digital Control Panel(s)

Digital Metering
 Engine Parameters
 Generator Protection Functions
 Engine Protection
 CAN Bus ECU Communications
 Windows-Based Software
 Multilingual Capability
 16 Programmable Contact Inputs
 Up to 11 Contact Outputs
 UL Recognized, CSA Certified, CE Approved
 Event Recording
 IP 54 Front Panel Rating with Integrated Gasket
 NFPA110 Compatible

* Represents standard product only. Consult Factory/MTU Onsite Energy Distributor for additional configurations.

APPLICATION DATA

// Engine

Manufacturer	MTU
Model	18V2000G85TB
Type	4-Cycle
Arrangement	18-V
Displacement: L (Cu In)	35.8 (2,186)
Bore: cm (in)	13 (5.1)
Stroke: cm (in)	15 (5.9)
Compression Ratio	16:1
Rated RPM: 60 Hz	1,800
Engine Governor	Electronic Isochronous (ADEC)
Max Power: 110% kWm (bhp)	1,310 (1,755)
Max Power: Prime kWm (bhp)	1,191 (1,597)
Speed Regulation	±0.25%
Air Cleaner	Dry

// Liquid Capacity (Lubrication)

Total Oil System: L (gal)	130 (34.3)
Engine Jacket Water Capacity: L (gal)	120 (31.7)
System Coolant Capacity: L (gal)	583 (154)
Fuel Capacity: L (gal)	3,785 (1,000)

// Electrical

Electric Volts DC	24
Cold Cranking Amps Under -17.8 °C (0 °F)	2,300

// Fuel System

Fuel Supply Connection Size	Quick Disconnect
Fuel Return Connection Size	Quick Disconnect
Maximum Fuel Lift: m (ft)	1 (3)
Recommended Fuel	Diesel #2
Total Fuel Flow: 60 Hz L/hr (gal/hr)	480 (146)

// Fuel Consumption

At 100% of Power Rating: L/hr (gal/hr)	284 (75)
At 75% of Power Rating: L/hr (gal/hr)	219 (58)
At 50% of Power Rating: L/hr (gal/hr)	149 (39)

// Cooling - Radiator System

Ambient Capacity of Radiator: °C (°F)	50 (122)
Max. Restriction of Cooling Air, Intake, and Discharge Side of Rad.: kPa (in. H ₂ O)	0.125 (0.5)
Water Pump Capacity: L/min (gpm)	867 (229)
Heat Rejection to Coolant: kW (BTUM)	460 (26,160)
Heat Rejection to After Cooler: kW (BTUM)	320 (18,200)
Heat Radiated to Ambient: BTUM (kW)	50 (2,841)

// Air Requirements

Aspirating: *(m ³ /min) SCFM	102 (3,605)
Air Flow Required for Rad.	
Cooled Unit: *(m ³ /min) SCFM	1,444 (51,000)
Remote Cooled Applications; Air Flow Required for Dissipation of Radiated Gen-set Heat for a Max of 25 °F Rise: *(m ³ /min) SCFM	N/A


* Air density = 1.184 kg/m³ (0.0739 lbm/ft³)

// Exhaust System

Gas Temp. (Stack): °C (°F)	510 (950)
Gas Volume at Stack Temp: m ³ /min (CFM)	240 (8,476)
Maximum Allowable Back Pressure: kPa (in. H ₂ O)	9 (34)

N/A = Not applicable to this system

WEIGHTS AND DIMENSIONS



Drawing above for illustration purposes only, based on standard open power 480 volt engine-generator set. Lengths may vary with other voltages. Do not use for installation design. See website for unit specific template drawings.

System	Dimensions (L x W x H)	Weight (wet/no fuel)
Power Module - Prime	12,192 x 2,439 x 2,896 mm (480 x 96 x 114 in)	29,120 kg (64,200 lb)

Weights and dimensions are based on open power units and are estimates only. Consult the factory for accurate weights and dimensions for your specific engine-generator set.

SOUND DATA

Unit Type	Full Load
Power Module - Prime	C/F

Sound data is provided at 7 m (23 ft). Engine-generator set tested in accordance with ISO 8528-10 and with infinite exhaust.

EMISSIONS DATA

NO _x + NMHC	CO	PM
5.158	0.0425	0.0238

All units are in g/hp-hr and at 100% load.

Emission levels of the engine may vary as a function of ambient temperature, barometric pressure, humidity, fuel type and quality, installation parameters, measuring instrumentation, etc. The data provided are laboratory results from one engine representing this rating. The data was obtained under controlled environmental conditions with calibrated instrumentation traceable to the United States National Bureau of Standards and in compliance with US EPA regulations found within 40 CFR Part 89. The weighted cycle value (not shown) from each engine is guaranteed to be below the US EPA Standards at the US EPA defined conditions.

RATING DEFINITIONS AND CONDITIONS

// Prime power ratings apply to installations where utility power is unavailable or unreliable. At varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour in twelve. Ratings are in accordance with ISO 8528-1, ISO 3046-1, BS 5514, AS 2789, and DIN 6271.

// Deration Factor:

Altitude: Consult your local MTU Onsite Energy Power Generation Distributor for altitude derations.

Temperature: Consult your local MTU Onsite Energy Power Generation Distributor for temperature derations.

Materials and specifications subject to change without notice.

C/F = Consult Factory/MTU Onsite Energy Distributor